

**6228B****EASYCOM HF INTERCOM, BLACK. SIMPLEBUS/KIT**

SB2

Hands-free door-entry phone with electronic call, call volume adjustment, privacy service, loudspeaker volume adjustment and conversation privacy. Fitted as standard with 3 buttons for audio operation, with audio active indicator LED, lock-release command and command for actuator Art. 1256. The buttons can be configured differently for switchboard call and actuator functions. Allows floor door call and call repetition management. Complete with dip-switch with 8 positions for selection of the desired user code. Door-entry phone for use in mixed audio/video Simplebus 1 and Simplebus 2 systems or in Simplebus KITS. Intercom function (to devices with the same address) in kit and Simplebus2 systems. Fitted with distribution terminal art. 1214/2C. It is compatible with all SBTOP functions and products. Allows direct intercommunication between users with the same address (without the aid of an interface or porter switchboard), separate call to main switchboard, secondary switchboard and guardian door-entry phone. Colour: black. Dimensions: 3.5"x6.3"x1.1"



6228B

EASYCOM HF INTERCOM, BLACK. SIMPLEBUS/KIT

MAIN FEATURES

Audio system:	Yes
Audio/video system:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Color:	Black RAL9005
Total buttons:	3
Backlighting color:	

FUNCTIONS

Actuator control function:	Yes
Switchboard call function:	Yes
Priority calls:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Privacy function:	Yes
Doctor:	Yes
Redial:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	Yes

SETTINGS

Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes

COMPATIBILITY

Simplebus 2 audio/video system:	Yes
---------------------------------	-----

TECHNICAL CHARACTERISTICS

Power supply voltage (VDC):	22 ÷ 28
Minimum current absorption (mA):	0.7
Maximum current absorption (mA):	400
Microphone:	9.6 (ø) x 9.6mm, omnidirectional
Loudspeaker:	



6228B

EASYCOM HF INTERCOM, BLACK. SIMPLEBUS/KIT

TECHNICAL CHARACTERISTICS

IP protection rating:	IP30
Operating temperature (°F):	41 ÷ 104
Weight (oz):	0.78
Clamps:	L L CFP CFP S- S+



6228B

EASYCOM HF INTERCOM, BLACK. SIMPLEBUS/KIT

ACCESSORIES



1214/2C

BRANCH TERMINAL FOR S2 SYSTEM

Line branch terminal. The terminal must be connected on the riser to be branched towards brackets or telephones.



1256

ACTUATOR RELAY

Intelligent Simplebus device for controlling a 10 A (12-24 V relay contact) on board. It can be used in Simplebus 1 and Simplebus 2 systems. Depending on the position of the jumper, the device provides six distinct functions: call repetition, activation on porter switchboard call pushbutton, door opening (without external unit), activation on actuator pushbutton, activation on actuator pushbutton with code. For use and programming of the function required, follow the indications given in the technical documentation. If used in mixed audio/video systems, the actuator relay needs terminal art. 1214/2 to be purchased separately. Power supply: 12V AC or 20V DC. Dimensions: 2.6"x3.3"x1.4". (4 DIN modules).



6212

DESK BASE FOR EASYCOM DOOR-ENTRY PHONE

Stainless steel desk base suitable for all Easycom door-entry phone versions.