

16/8 VIDEO INPUTS STANDALONE DIGITAL VIDEO RECORDER

ART.49146/49148



Specifications:

- Video mode: PAL/NTSC.
 - Video inputs: 16/8 composite video with BNC connectors, auto-terminated, 1Vpp / 75 ohm.
 - Recording frame rate: 100 IPS (PAL), 120 IPS (NTSC)
 - Display frame rate: 400 IPS (PAL), 480 IPS (NTSC)
 - Video outputs: 3, 2 composite video with BNC connectors, 1 S-Video
 - Video compression: M-JPEG
 - Video effects: zoom, watermark protection
 - Network card: integrated, speed 10/100 Mbps (RJ45 connector)
 - Alarm inputs: 16/8 programmables
 - Alarm output: 1
 - Audio inputs: 4, RCA connectors
 - Audio output: 2, RCA connectors
 - HDD: 2 ATA-100 each over 200 GB (**NOTE: NOT in equipment**)
 - Other functions: backup through CD-RW and/or HDD USB (**NOT in equipment**) and/or network; upgrade through USB; RS485 for PTZ control
 - Search and record: date, event (video loss, external alarm and motion detector), time-lapse, schedule
 - Power supply: from 100 to 240 Vac 50/60 Hz
 - Consumption: 36W (art.49148), 39.6W (art.49146)
 - Dimensions: (W x H x D): 430 x 65 x 385 mm
 - Weight: 5.4 Kg (without power supply)
 - Operating temperature: from -5° to +40° C
 - Humidity : < 90% non condensing
 - Accessories in equipment: remote control, remote viewer software, DVR and remote viewer software manual instructions, power supply.
- The specifications are subject to variations without warning