



3022/2/RI/B

ROMA SERIES AUDIO ENT. PANEL FOR IKALL UNIT, 22 BUTT.-BRONZE



Door-entry phone entrance panel with bronze finish front plate in 3 mm thick watchmaking brass plate with PVD treatment. Complete with flush-mounted box and anti-intrusion screws. All entrance panels are fitted with bulb sockets (without bulb) for festoon bulbs with a diameter of 6.3 x 39 mm. The keypad should be finished with an audio speaker unit depending on the wiring system used. 22 buttons, 2 rows. Plate dimensions 180x477x3 mm. Box dimensions 160x420x55 mm. 4 lamp sockets



3022/2/RI/B

ROMA SERIES AUDIO ENT. PANEL FOR IKALL UNIT, 22 BUTT.-BRONZE

GENERAL DATA

Height (mm):	477
Width (mm):	180
Depth (mm):	3

COMPATIBILITY

Simplebus 2 audio/video system:	Yes
Simplebus 2 audio system:	Yes
Traditional system:	Yes
Simplified system:	Yes
Comelbus system:	Yes
Comtel system:	Yes



3022/2/RI/B

ROMA SERIES AUDIO ENT. PANEL FOR IKALL UNIT, 22 BUTT.-BRONZE

ACCESSORIES



1172

VANDALCOM 12/24V BULBS
24V/3W festoon bulb for illuminating name labels.



1622VC

IKALL COLOUR REMOTE CAMERA AUDIO MODULE SB2 COLOUR

Module which allows modulation and transmission of the colour video signal on the riser. On input it has the composite video signal of a colour camera. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33400, 33401 and 33402. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. It allows call addressing for up to 120000 users. Timed lock-release inputs and door open indication.



1682HVC

IKALL SERIES AUDIO MOD. FOR REM.COL.CAM. VIP. H264

Vip system audio unit with facility for connection of a remote camera with 12Vdc power supply. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume adjustable from the front. Dimensions: 102x55x38 mm. Compatible with H.264 video format.