



IPSWR030A

REPEATER, 3 POE GIGABIT PORTS



Network repeater, 3 Gigabit ports, 1 input port (PD) for the PoE network cable, 2 output ports (PSE) to connect the PoE devices (30W max).
No power supply required.

MAIN FEATURES

- Support the PoE standard IEEE802.3at and IEEE802.3af
- Supports IEEE 802.3x flow control for full-duplex mode and back-pressure for half-duplex mode
- 2 ports (PSE) to supply power to 2 PoE devices
- MAC address table with auto-learning and auto-aging functions
- Power supply via standard PoE cable (1 PD port)



IPSWR030A

REPEATER, 3 POE GIGABIT PORTS

MAIN FEATURES

LAN ports:	3 PoE Gigabit (RJ-45, auto MDI/MDI-X, 1 IN (PD), 2 OUT (PSE-30W))
Standards / Protocols Supported:	IEEE802.3af/at/ab/az, IEEE802.3x(full-d./back pressure(half-d.))
Transfer method:	Store and Forward
Exchange capacity (Gb/s):	6
MAC address:	Auto-learning, auto-update
Frame Filtering and Forward Rate:	

GENERAL DATA

Height (mm):	27
Width (mm):	134,7
Depth (mm):	77
Type of finish:	
Colour:	White
Operating temperature (°C):	-10 ÷ 40
RH max operating humidity (%):	90