



**VEDO200EN**

**VEDO 200, PLASTIC BOX, 1.5A POW.SUPP.UNIT, ENGLISH**



VEDO switchboard in wall-mounted, flame-resistant, ABS housing with 1.5A switching power supply unit. Equipped with 8 on-board zones, expandable to 68 mixed wired/radio zones, 1 24-hour zone, double function for a maximum of 136 zones, integrated PSTN telephone dialler, RS485 serial bus for the connection of additional modules, 1 relay output and 2 open collector outputs. Manages up to 8 areas with 16 different activation programmes (scenarios) and daily timers, 12 IN/OUT expansions, 8 proximity readers, 8 Safekey keypads, 4 Safetouch, 4 Planux/Mini Touch manager and 3 radio receivers. Self-resettable fuse for the siren power supply output, RS485 serial bus and sensor power supply. Equipped with USB port for connection to the PC with Safe Manager configuration software. All zones are configurable as NC, NO, single, double and triple balance and as double zone. Dimensions (LxHxD) 260x280x80mm.


**VEDO200EN**
**VEDO 200, PLASTIC BOX, 1.5A POW.SUPP.UNIT, ENGLISH**
**MAIN FEATURES**

Number of inputs on board:	8
Double function:	Yes
Number of zone max (Double function):	400
Balance type:	NA, NC, Single, Double, Triple, Anti-blinding, Double, EOL
Number radio zone:	200
Number of outputs:	100
Number of relay outputs on central board:	1 (3A@24VDC)
Number TC outputs on central board:	2
Areas number:	16
Number of user codes:	200
Number installer codes:	6
Partial controls managed:	2
Number of insertion programs (scenarios):	32
Number of time slots:	32
Number of timer:	32
Audio Messaging - Text to speech:	48
Central programming:	USB, LAN

**COMMUNICATION**

Phone numbers managed by the digital communicator:	4
Phone numbers managed by vocal communicator:	16
Bus type of connections:	RS485
Maximum number of e-mail addresses:	16
Built-in digital communicator:	Yes
Management interface of the vocal guide:	Yes

**SOFTWARE/FIRMWARE SPECIFICATIONS**

APP:	Vedo
Desktop:	Safe Manager

**HARDWARE SPECIFICATIONS**

Height (mm):	275
Width (mm):	255
Depth (mm):	75
Weight (g):	1700
Operating temperature (°C):	-10 ÷ 55
Case:	
Type of finish:	ABS



**VEDO200EN**

**VEDO 200, PLASTIC BOX, 1.5A POW.SUPP.UNIT, ENGLISH**

**HARDWARE SPECIFICATIONS**

Tamper protection:	Yes
Power supply (A):	1

**MODULE EXPANSION ON BUS**

Number expansions IN / OUT:	50
Number proximity reader:	16
Number Safekey keyboards:	16
Number Safetouch keyboards:	4
Number of supervisor manager:	4
Number radio receivers:	8
Number modules image conversion PAL / IP:	4
Number cameras managed:	32

**MODULE EXPANSION PLUG**

Audio module:	Yes
GSM module:	Yes
IP Module:	Yes

**ELECTRICAL SPECIFICATIONS**

Supply voltage (VAC):	100÷240
Current supplied from the control unit (mA):	1500
Number auxiliary power outputs on board:	2
Battery type expected:	12V / 7Ah



**VEDO200EN**

**VEDO 200, PLASTIC BOX, 1.5A POW.SUPP.UNIT, ENGLISH**

ACCESSORIES



**VED034**

**VEDO 34 CONTROL PANEL, PLASTIC BOX, 1.5 A POWER SUPPLY UNIT**

VEDO switchboard in wall-mounted, flame-resistant, ABS housing with 1.5A switching power supply unit. Equipped with 8 on-board zones, expandable to 34 mixed wired/radio zones, 1 24-hour zone, double function for a maximum of 68 zones, integrated PSTN telephone dialler, RS485 serial bus for the connection of additional modules, 1 relay output and 2 open collector outputs. Manages up to 8 areas with 8 different activation programmes (scenarios) and daily timers, 8 IN/OUT expansions, 8 proximity readers, 8 Safekey keypads, 2 Safetouch, 2 Planux/Mini Touch manager and 2 radio receivers. Self-resettable fuse for the siren power supply output, RS485 serial bus and sensor power supply. Equipped with USB port for connection to the PC with Safe Manager configuration software. All zones are configurable as NC, NO, single, double and triple balance and as double zone. Dimensions (LxHxD) 260x280x80mm.