



AHCAM638AWDR

AHD FULL-HD MINIDOME CAMERA, 2.8-12MM WDR



Minidome AHD Day & Night colour camera, 2.8-12 mm varifocal lens, FULL-HD (1080p) resolution, 2 megapixel, case IP66 waterproof, 36 infrared leds with range of up to 30 meters.


AHCAM638AWDR
AHD FULL-HD MINIDOME CAMERA, 2.8-12MM WDR
MAIN FEATURES

Camera sensor:	1/2.8" CMOS
Effective pixels (H x V - pixels):	1945x1097
Camera lens:	
Electronic shutter (s):	1/25 ÷ 1/10000
Signal/noise ratio (dB):	>50 (AGC OFF)
IR filter:	Mechanical
Video output:	AHD/TVI/CVI/CVBS (960H)
Video resolution (H x V - pixel):	1920x1080 (Full-HD 1080p)

FUNCTIONS

Main functions:	3DNR, BLC
Back light compensation (BLC):	BLC
Wide Dynamic Range WDR (dB):	WDR (120dB)
Enhanced DNR control:	3DNR
White balance control:	ATW/AWB
Exposure control:	AE
Camera tilting:	Yes

HARDWARE SPECIFICATIONS

No. IR LEDs / Max. distance (m):	24 led SMD / 35m
Maximum cable distance RG59 / UTP (m):	300 / 100

GENERAL DATA

Power supply voltage (VDC):	12
Max absorption (W):	4,8
Diameter (mm):	119
Height (mm):	83
Weight (g):	580
Housing type:	Minidome
Operating temperature (°C):	-25 ÷ 50
RH max operating humidity (%):	85



AHCAM638AWDR

AHD FULL-HD MINIDOME CAMERA, 2.8-12MM WDR

ACCESSORIES



WM100SD

MINIDOME WALL MOUNTING SUPPORT

Support for wall mounting of minidome cameras art. IPCAM122A, IPCAM124A, IPCAM172A, IPCAM174A, IPCAM1838A, IPCAM1848A, IPCAM184KA, AHCAM634ZA, AHCAM637C, AHCAM638AWDR, AHCAM638B, AHCAM638ZA, AHCAM639ZB, AHCAM1858ZA, AHCAM175ZA, AHCAM125A and connection boxes art. JB-100MDA and JB-100SMDA, white color.



43082

POWER SUPPLY, JACK CONNECTOR, 230VAC/12VDC, 1.33A

Plug power supply, input from 100 to 240 VAC/50-60 Hz, output 12 VDC/1.33A with jack connector.