



1256

ACTUATOR RELAY



SB2

Intelligent Simplebus device for controlling a 10 A (12-24 V relay contact) on board. It can be used in Simplebus 1 and Simplebus 2 systems. Depending on the position of the jumper, the device provides six distinct functions: call repetition, activation on porter switchboard call pushbutton, door opening (without external unit), activation on actuator pushbutton, activation on actuator pushbutton with code. For use and programming of the function required, follow the indications given in the technical documentation. If used in mixed audio/video systems, the actuator relay needs terminal art. 1214/2 to be purchased separately. Power supply: 12V AC or 20V DC. Dimensions: 2.6"x3.3"x1.4". (4 DIN modules).



1256

ACTUATOR RELAY

MAIN FEATURES

Height (inch):	3.27
Width (inch):	2.6
Depth (inch):	1.46
Operating temperature (°F):	14 ÷ 86
DIN rail mounted:	Yes
DIN modules (no.):	4
Maximum current absorption (mA):	50

COMPATIBILITY

Simplebus 2 audio/video system:	Yes
Building Kit audio/video system:	Yes
Simplebus 2 audio system:	Yes
Simplebus 1 audio system:	Yes
Kit audio/video system:	Yes

AUDIO/VIDEO FEATURES

Audio system:	Yes
Audio/video system:	Yes