



4888CU

SIMPLEBUS 2 COLOUR MIXER FOR USA



SB2

The mixer is contained in a 8 DIN module box. Supplied from 110V mains, it has a dedicated output for power supply switching device art. 1224A. On input it receives a Simplebus 2 type signal and superimposes the monitor power supply for the riser. Up to 100 pieces of apparatus between telephones and monitors can be connected, distributed over 4 outputs. Fitted with LED which signals any short-circuits on the lines. Fitted with 4 terminals for line termination art. 1216. Dimensions: 5.5"x5.5"x2.6". (8 DIN modules).



4888CU

SIMPLEBUS 2 COLOUR MIXER FOR USA

MAIN FEATURES

Height (inch):	2.6
Width (inch):	5.51
Depth (inch):	5.51
DIN rail mounted:	Yes
DIN modules (no.):	8

HARDWARE SPECIFICATIONS

Visual signalling:	Yes
--------------------	-----

GENERAL DATA

Type of finish:	
Color:	



4888CU

SIMPLEBUS 2 COLOUR MIXER FOR USA

ACCESSORIES



1216

LINE TERMINATION TERMINAL

Line termination terminal. Provided as standard with mixer art.4888CU. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.