

**CHDS-42****SPLITTER 4X2**

This 4x2 HDMI Matrix Switch lets you connect up to 4 HDMI inputs and 2 HDMI outputs. It is a true Matrix and can distribute any one of 4 sources to either of the 2 displays connected. This unit can also work as a splitter, to show the same source on 2 displays simultaneously. It is great for Residential and commercial applications. - Input Video Signal: 0.5 -1.0 volts p-p. - Input DDC Signal: 5 volts p-p (TTL). - Max Single Link Range: 1920x1080, 1080P. - HDMI Resolution 480i/576i/480p/576p/720p/1080i/1080P/3D (1080P/24Hz). - DVI Resolution: 480p/576i/576p/720p/1080i/1080p. - HDMI Version: HDMI 1.3b. - Bandwidth: Up to 225MHz. - EDID Duration: 6 seconds. - Power Consumption: DC 5V@1A. - Power supply, DC 5V@1A. - Max Cable Extension: 30 ft. for 28AWG HDMI Cable 45 ft. for 26AWG HDMI Cable. - Operating Temperature: 14-140 F. - Dimension: mm 20x9.8x2.



**CHDS-42**

**SPLITTER 4X2**

MAIN FEATURES

Height (inch):	0.03
Width (inch):	0.31
Depth (inch):	0.14

GENERAL DATA

Type of finish:	
Unit of measurement:	Inches