



IPSWP240A

SWITCH, 24 POE PORTS



Network switch with 24 PoE ports, max 260W total. Is possible to connect 24 Mini hands-free monitors, or 24 Icona monitors or 12 Maxi monitors. Dimensions 17.53"x8.25"x0.17".

MAIN FEATURES

- Power supplied: 260W max total
- Support the PoE standard IEEE802.3at
- Supports IEEE 802.3x flow control for full-duplex mode and back-pressure for half-duplex mode
- Exchange capacity 4.8 Gbit/s
- Speed and transmission auto-negotiation
- MAC address table with auto-learning and auto-aging functions
- Store-and-Forward transfer method



IPSWP240A

SWITCH, 24 POE PORTS

MAIN FEATURES

Standards / Protocols Supported:	IEEE802.3u, IEEE802.3x (full-duplex)/back pressure (half-duplex)
LAN PoE ports:	24 (10/100Mbit/s), 48 VDC (260W max), standard IEEE802.3af/at
Transfer method:	Store and Forward
Exchange capacity (Gb/s):	4.8
MAC address:	Auto-learning, auto-update
Frame Filtering and Forward Rate:	

GENERAL DATA

Power supply voltage (VAC):	
Height (inch):	1.73
Width (inch):	17.4
Depth (inch):	8.19
Type of finish:	Metallic
Color:	
Operating temperature (°F):	14 ÷ 104
RH max operating humidity (%):	90
Supplied accessories:	Rack mounting brackets